

Supercoat™ Coating System

200, 250 or 300mm external Supercrete™ Block walls

Supercoat™ Superbond adhesive in thickness as required for leveling

Cast in-situ 17.5 MPa concrete combined ring anchor/bond beam

50 or 100mm Supercrete™ Facing Block to type 2, 5 or 7 bond beams

40mm min

70mm min (end support)

150, 200 or 250mm Supercrete™ Structural Floor panels

Suspended ceiling system, battens connected to hangers fixed over ring anchor bars

Selected ceiling lining

Interior lining system Supercoat™ Coating System or plasterboard

Supercoat™ Tanking Membrane over block walls in all tiled showers

Ceramic wall tiles fixed over walls with tile adhesive

Floor tiles on tile adhesive

Supercoat™ Tanking membrane (refer to Supercoat™ specifications)

Fall created with Supercoat™ Superbuild Render or similar mortar bed

External Wall/Floor Panel End Support Detail (Upstairs Wet Area example shown)

Copyright © Superbuild International Ltd 2013

Supercrete™
SFP CONSTRUCTION

Title: Structural Floor Panel
External Wall/Floor Panel End Detail

Date: September 2013

Scale: 1:5

Detail No. SFP 2-7

This drawing must be read in conjunction with all the Supercrete Structural Floor Panels Design Guide