



SupercreteTM

Soundfloor Joist Chart

SupercoatTM

Copyright © Supercrete Limited 2008

Without limiting the rights of the copyright above, no part of this publication shall be reproduced (whether in the same or a different dimension), stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording or otherwise), without the prior permission of the copyright owner.

Timber Joists for Supercrete™ Soundfloor

Table 1

Minimum Joist Sizes for L/250 Deflection Maximum															
1.5 kPa Live Load															
Framing Type	Dry No. 1 & MSG6			Dry VSG8 & MSG8			Dry VSG10 & MSG10			Dry MSG12			Dry MSG15		
	Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)		
Span (m)	360	450	600	360	450	600	360	450	600	360	450	600	360	450	600
1.2	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35
1.5	140 x 45	140 x 45	140 x 45	90 x 45	140 x 45	140 x 45	90 x 45	90 x 45	140 x 45	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 35
1.8	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	90 x 45	140 x 45	140 x 45	90 x 45	90 x 45	140 x 45
2.1	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45
2.4	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45
2.7	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45
3.0	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
3.3	240 x 45	240 x 45	290 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
3.6	240 x 45	290 x 45		240 x 45	240 x 45	290 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45
3.9	290 x 45			240 x 45	290 x 45		240 x 45	240 x 45	290 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45
4.2				290 x 45			240 x 45	290 x 45		240 x 45	240 x 45	240 x 45	240 x 45	240 x 45	240 x 45
4.5							290 x 45	290 x 45		240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45
4.8										240 x 45	290 x 45		240 x 45	240 x 45	290 x 45

2.0 kPa Live Load															
Framing Type	Dry No. 1 & MSG6			Dry VSG8 & MSG8			Dry VSG10 & MSG10			Dry MSG12			Dry MSG15		
	Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)		
Span (m)	360	450	600	360	450	600	360	450	600	360	450	600	360	450	600
1.2	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35
1.5	140 x 45	140 x 45	140 x 45	90 x 45	140 x 45	140 x 45	90 x 45	90 x 45	140 x 45	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 35
1.8	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	90 x 45	140 x 45	140 x 45	90 x 45	90 x 45	140 x 45
2.1	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45
2.4	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	190 x 45
2.7	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45
3.0	240 x 45	240 x 45	290 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
3.3	240 x 45	290 x 45		190 x 45	240 x 45	290 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45
3.6	290 x 45			240 x 45	240 x 45		240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45
3.9				290 x 45			240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45
4.2							240 x 45	290 x 45		240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45
4.5							290 x 45			240 x 45	290 x 45		240 x 45	240 x 45	290 x 45
4.8										290 x 45			240 x 45	290 x 45	290 x 45

3.0 kPa Live Load															
Framing Type	Dry No. 1 & MSG6			Dry VSG8 & MSG8			Dry VSG10 & MSG10			Dry MSG12			Dry MSG15		
	Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)		
Span (m)	360	450	600	360	450	600	360	450	600	360	450	600	360	450	600
1.2	90 x 45	90 x 45	140 x 45	90 x 35	90 x 35	90 x 45	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35	90 x 35
1.5	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	90 x 45	140 x 45	140 x 45	90 x 35	90 x 45	140 x 45	90 x 35	90 x 35	90 x 45
1.8	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45
2.1	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45
2.4	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45
2.7	190 x 45	240 x 45	290 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
3.0	240 x 45	290 x 45		190 x 45	240 x 45	290 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45
3.3	290 x 45			240 x 45	290 x 45		240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45
3.6				290 x 45			240 x 45	240 x 45		240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45
3.9							240 x 45	290 x 45		240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45
4.2							290 x 45			240 x 45	290 x 45		240 x 45	240 x 45	290 x 45
4.5										290 x 45			240 x 45	290 x 45	290 x 45
4.8										290 x 45			290 x 45	290 x 45	

NOTES

- 1) These tables refer to Pinus Radiata only.
- 2) These tables are for single spans. Continuous joists over two or more spans may have allowable spans increased by 10%.
- 3) Where a load-bearing wall runs parallel to the line of joists, the wall must be supported on double joists with a maximum width spacer of 50 mm between them.
- 4) Where a load-bearing wall is perpendicular to the line of joists, the centre of the wall must be no more than 200 mm from the centre of the bearer supporting the joists.
- 5) Cantilevered joists must be specifically designed.
- 6) Joists with moisture content in excess of 16% must be propped until the moisture content is 16% or less.
- 7) Where 35 mm thick joists are used, panel end joints must be on double joists.
- 8) These tables allow for a ceiling dead load of 260 N/m² (12 mm plasterboard on battens).
- 9) These tables include the effect of a 1.8 kN concentrated live load as required by NZS 4203.

In most cases, joist size is governed by deflection. Some larger spans are governed by bending capacity.

Timber Joists for Supercrete™ Soundfloor

Table 2

Minimum Joist Sizes for L/600 Deflection Maximum															
1.5 kPa Live Load															
Framing Type	Dry No. 1 & MSG6			Dry VSG8 & MSG8			Dry VSG10 & MSG10			Dry MSG12			Dry MSG15		
	Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)		
Span (m)	360	450	600	360	450	600	360	450	600	360	450	600	360	450	600
1.2	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	90 x 45	90 x 45	90 x 45	90 x 45	90 x 45	90 x 45
1.5	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45
1.8	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45
2.1	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45
2.4	240 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
2.7	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45
3.0	290 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	240 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45
3.3	290 x 45	290 x 45		290 x 45	290 x 45	290 x 45	240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45
3.6				290 x 45	290 x 45		290 x 45	290 x 45	290 x 45	240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45
3.9				290 x 45			290 x 45	290 x 45		290 x 45	290 x 45		240 x 45	290 x 45	290 x 45
4.2										290 x 45	290 x 45		290 x 45	290 x 45	
4.5										290 x 45			290 x 45	290 x 45	
4.8													290 x 45		

2.0 kPa Live Load															
Framing Type	Dry No. 1 & MSG6			Dry VSG8 & MSG8			Dry VSG10 & MSG10			Dry MSG12			Dry MSG15		
	Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)		
Span (m)	360	450	600	360	450	600	360	450	600	360	450	600	360	450	600
1.2	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	90 x 45	90 x 45	140 x 45	90 x 45	90 x 45	90 x 45
1.5	190 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45
1.8	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	190 x 45
2.1	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
2.4	240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
2.7	240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45
3.0	290 x 45	290 x 45		240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	240 x 45	240 x 45	240 x 45
3.3	290 x 45			290 x 45	290 x 45		240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	290 x 45
3.6				290 x 45			290 x 45	290 x 45		290 x 45	290 x 45	290 x 45	240 x 45	290 x 45	290 x 45
3.9							290 x 45			290 x 45	290 x 45		290 x 45	290 x 45	
4.2										290 x 45			290 x 45	290 x 45	
4.5													290 x 45		
4.8													290 x 45		

3.0 kPa Live Load															
Framing Type	Dry No. 1 & MSG6			Dry VSG8 & MSG8			Dry VSG10 & MSG10			Dry MSG12			Dry MSG15		
	Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)			Joist Spacing (mm)		
Span (m)	360	450	600	360	450	600	360	450	600	360	450	600	360	450	600
1.2	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	140 x 45	90 x 45	140 x 45	140 x 45	90 x 45	90 x 45	140 x 45
1.5	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	190 x 45	140 x 45	140 x 45	140 x 45
1.8	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	140 x 45	190 x 45	190 x 45
2.1	240 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45	190 x 45
2.4	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45	190 x 45	190 x 45	240 x 45	190 x 45	190 x 45	240 x 45
2.7	290 x 45	290 x 45		240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	240 x 45	190 x 45	240 x 45	240 x 45
3.0	290 x 45			290 x 45	290 x 45		240 x 45	290 x 45	290 x 45	240 x 45	240 x 45	290 x 45	240 x 45	240 x 45	290 x 45
3.3				290 x 45			290 x 45	290 x 45		290 x 45	290 x 45	290 x 45	240 x 45	290 x 45	290 x 45
3.6							290 x 45			290 x 45	290 x 45		290 x 45	290 x 45	290 x 45
3.9										290 x 45			290 x 45	290 x 45	
4.2													290 x 45		
4.5													290 x 45		
4.8													290 x 45		

NOTES Refer to Table 1 for notes.

Steel Joists Profiles for Supercrete™ Soundfloor

Table 3

Minimum Steel Joist Sizes for L/250 Deflection Maximum											
1.5 kPa Live Load				2.0 kPa Live Load				3.0 kPa Live Load			
Span (m)	Joist Spacing (mm)			Span (m)	Joist Spacing (mm)			Span (m)	Joist Spacing (mm)		
	360	450	600		360	450	600		360	450	600
1.2	60 x .95 TH	60 x .95 TH	60 x .95 TH	1.2	100 x .75 TH	100 x .75TH	100 x .75 TH	1.2	60 x .95 TH	60 x .95 TH	60 x .95 TH
1.5	100 x .75 TH	100 x .75 TH	100 x .75 TH	1.5	100 x .75 TH	100 x .75TH	100 x .75 TH	1.5	100 x .75 TH	100 x .75 TH	100 x .75 TH
1.8	100 x .75 TH	100 x .75 TH	100 x .75 TH	1.8	100 x .75 TH	100 x .75TH	100 x .75 TH	1.8	100 x .75 TH	100 x .75 TH	100 x .75 TH
2.1	100 x .75 TH	100 x .75 TH	100 x .75 TH	2.1	100 x .75 TH	100 x .95 TH	120 x .95 TH	2.1	100 x .75 TH	100 x .75 TH	100 x .95 TH
2.4	100 x .75 TH	100 x .75 TH	100 x .95 TH	2.4	100 x .95 TH	120 x .95 TH	120 x .95 TH	2.4	100 x .95 TH	120 x .95 TH	120 x .95 TH
2.7	100 x .95 TH	100 x .95 TH	120 x .95 TH	2.7	120 x .95 TH	150 x .95 TH	150 x .95 TH	2.7	120 x .95 TH	120 x .95 TH	150 x .95 TH
3.0	120 x .95 TH	120 x .95 TH	150 x .95 TH	3.0	150 x .95 TH	150 x .95 TH	150 x .95 TH	3.0	150 x .95 TH	150 x .95 TH	150 x .95 TH
3.3	120 x .95 TH	150 x .95 TH	150 x .95 TH	3.3	150 x .95 TH	150 x .95 TH	150 x .95 TH	3.3	150 x .95 TH	150 x .95 TH	150/15 C
3.6	150 x .95 TH	150 x .95 TH	150 x 1.15 TH	3.6	150 x .95 TH	150 x 1.15 TH	150/15 C	3.6	150 x 1.15 TH	150/15 C	200/12 C
3.9	150 x .95 TH	150 x 1.15 TH	150/15 C	3.9	150 x 1.15 TH	150/15 C	150/18 C	3.9	150/15 C	200/12 C	200/12 C
4.2	150 x 1.15 TH	150/15 C	150/18 C	4.2	150/15 C	150/18 C	200/12 C	4.2	150/15 C	200/12 C	200/15 C
4.5	150/15 C	150/18 C	200/12 C	4.5	150/18 C	200/12 C	200/12 C	4.5	200/12 C	200/12 C	200/18 C
4.8	150/18 C	200/12 C	200/12 C	4.8	200/12 C	200/12 C	200/15 C	4.8	200/12 C	200/15 C	250/15 C
5.1	200/12 C	200/12 C	200/15 C	5.1	200/12 C	200/15 C	200/18 C	5.1	200/15 C	200/18 C	250/15 C
5.4	200/12 C	200/15 C	200/18 C	5.4	200/15 C	200/18 C	250/15 C	5.4	200/18 C	250/15 C	250/15 C
5.7	200/15 C	200/18 C	250/15 C	5.7	200/18 C	250/15 C	250/15 C	5.7	250/15 C	250/15 C	250/18 C
6.0	200/18 C	250/15 C	250/15 C	6.0	250/15 C	250/15 C	250/18 C	6.0	250/15 C	250/18 C	300/15 C
6.3	200/18 C	250/15 C	250/15 C	6.3	250/15 C	250/15 C	250/18 C	6.3	250/15 C	250/18 C	300/15 C
6.6	250/15 C	250/15 C	250/15 C	6.6	250/15 C	250/18 C	300/15 C	6.6	250/18 C	300/15 C	300/18 C
6.9	250/15 C	250/18 C	300/15 C	6.9	250/18 C	300/15 C	300/15 C	6.9	300/15 C	300/15 C	300/18 C
7.2	250/15 C	250/18 C	300/15 C	7.2	250/18 C	300/15 C	300/15 C	7.2	300/15 C	300/18 C	350/18 C
7.5	250/18 C	300/15 C	300/15 C	7.5	300/15 C	300/15 C	300/15 C	7.5	300/15 C	300/18 C	350/18 C
7.8	300/15C	300/15 C	300/18 C	7.8	300/15 C	300/18 C	350/18 C	7.8	300/18 C	350/18 C	350/18 C
8.1	300/15C	300/15 C	350/18 C	8.1	300/15 C	300/18 C	350/18 C	8.1	350/18 C	350/18 C	400/20 C
8.4	300/15C	300/18 C	350/18 C	8.4	300/18 C	350/18 C	350/18 C	8.4	350/18 C	350/18 C	400/20 C
8.7	300/18C	350/18 C	350/18 C	8.7	300/18 C	350/18 C	400/20 C	8.7	350/18 C	400/20 C	400/20 C
9.0	300/18C	350/18 C	350/18 C	9.0	350/18 C	350/18 C	400/20 C	9.0	350/18 C	400/20 C	400/20 C

NOTES

- 1) These Tables are for HST steel sections. TH refers to Top Hat sections and C refers to channel sections as shown on Table 5 below.
- 2) Short span sizes make allowance for a 1.8 kN concentrated load (as required by NZS 4203) where deflection or bending stress is higher with the concentrated load than the uniformly distributed load.
- 3) These tables are for single spans. Continuous joists over two or more spans may have allowable spans increased by 10%.
- 4) Where a load-bearing wall runs parallel to the line of joists, wall must be supported on double joists with a maximum clear width of 50 mm between them.
- 5) Where a load-bearing wall is perpendicular to the line of joists, the centre of the wall must be no more than 200 mm from the centre of the bearer supporting the joists.
- 6) Cantilevered joists must be specifically designed.
- 7) These tables allow for a ceiling dead load of 260n/m² (12 mm plasterboard on battens).

Steel Joists Profiles for Supercrete™ Soundfloor

Table 4


Minimum Steel Joist Sizes for L/600 Deflection Maximum											
1.5 kPa Live Load				2.0 kPa Live Load				3.0 kPa Live Load			
Span (m)	Joist Spacing (mm)			Span (m)	Joist Spacing (mm)			Span (m)	Joist Spacing (mm)		
	360	450	600		360	450	600		360	450	600
1.2	100 x .75 TH	100 x .75 TH	100 x .75 TH	1.2	100 x .75 TH	100 x .75 TH	100 x .75 TH	1.2	100 x .75 TH	100 x .75 TH	100 x .75 TH
1.5	100 x .75 TH	100 x .75 TH	100 x .75 TH	1.5	100 x .75 TH	100 x .75 TH	100 x .75 TH	1.5	100 x .75 TH	100 x .75 TH	100 x .75 TH
1.8	100 x .95 TH	100 x .95 TH	120 x .95 TH	1.8	100 x .95 TH	100 x .95 TH	120 x .95 TH	1.8	100 x .95 TH	120 x .95 TH	120 x .95 TH
2.1	120 x .95 TH	120 x .95 TH	120 x .95 TH	2.1	120 x .95 TH	120 x .95 TH	150 x .95 TH	2.1	120 x .95 TH	150 x .95 TH	150 x .95 TH
2.4	120 x .95 TH	150 x .95 TH	150 x .95 TH	2.4	150 x .95 TH	150 x .95 TH	150 x .95 TH	2.4	150 x .95 TH	150 x .95 TH	150/15 C
2.7	150 x .95 TH	150 x .95 TH	150 x 1.15 TH	2.7	150 x .95 TH	150 x 1.15 TH	150/15 C	2.7	150 x 1.15 TH	150/15 C	200/12 C
3.0	150 x .95 TH	150 x 1.15 TH	150/15 C	3.0	150 x 1.15 TH	150/15 C	150/18 C	3.0	200/12 C	200/12 C	200/12 C
3.3	150/15 C	150/18 C	200/12 C	3.3	150/18 C	200/12 C	200/12 C	3.3	200/12 C	200/12 C	200/15 C
3.6	150/18 C	200/12 C	200/12 C	3.6	200/12 C	200/12 C	200/15 C	3.6	200/15 C	200/15 C	250/15 C
3.9	200/12 C	200/15 C	200/18 C	3.9	200/12 C	200/15 C	200/18 C	3.9	200/18 C	250/15 C	250/15 C
4.2	200/15 C	200/18 C	250/15 C	4.2	200/15 C	200/18 C	250/15 C	4.2	250/15 C	250/15 C	250/18 C
4.5	200/18 C	250/15 C	250/15 C	4.5	250/15 C	250/15 C	250/18 C	4.5	250/15 C	250/18 C	300/15 C
4.8	250/15 C	250/15 C	250/18 C	4.8	250/15 C	250/15 C	300/15 C	4.8	250/18 C	300/15 C	300/15 C
5.1	250/15 C	250/18 C	300/15 C	5.1	250/15 C	250/18 C	300/15 C	5.1	300/15 C	300/15 C	300/18 C
5.4	250/18 C	250/18 C	300/15 C	5.4	250/18 C	300/15 C	300/18 C	5.4	300/15 C	300/18 C	350/18 C
5.7	250/18 C	300/15 C	300/18 C	5.7	300/15 C	300/15 C	350/18 C	5.7	300/18 C	350/18 C	350/18 C
6.0	300/15 C	300/15 C	300/18 C	6.0	300/15 C	300/18 C	350/18 C	6.0	350/18 C	350/18 C	400/20 C
6.3	300/15 C	300/18 C	350/18 C	6.3	300/18 C	350/18 C	350/18 C	6.3	350/18 C	350/18 C	400/20 C
6.6	300/18 C	350/18 C	350/18 C	6.6	350/18 C	350/18 C	400/20 C	6.6	350/18 C	400/20 C	400/20 C
6.9	350/18 C	350/18 C	400/20 C	6.9	350/18 C	350/18 C	400/20 C	6.9	400/20 C	400/20 C	
7.2	350/18 C	350/18 C	400/20 C	7.2	350/18 C	400/20 C	400/20 C	7.2	400/20 C	400/20 C	
7.5	350/18 C	400/20 C	400/20 C	7.5	400/20 C	400/20 C		7.5	400/20 C		
7.8	350/18 C	400/20 C	400/20 C	7.8	400/20 C	400/20 C		7.8	400/20 C		
8.1	400/20 C	400/20 C		8.1	400/20 C			8.1			
8.4	400/20 C	400/20 C		8.4	400/20 C			8.4			
8.7	400/20 C			8.7				8.7			
9.0				9.0				9.0			

NOTES

- 1) These Tables are for HST steel sections. TH refers to Top Hat sections and C refers to channel sections as shown on Table 5 below.
- 2) Short span sizes make allowance for a 1.8 kN concentrated load (as required by NZS 4203) where deflection or bending stress is higher with the concentrated load than the uniformly distributed load.
- 3) These tables are for single spans. Continuous joists over two or more spans may have allowable spans increased by 10%.
- 4) Where a load-bearing wall runs parallel to the line of joists, wall must be supported on double joists with a maximum clear width of 50 mm between them.
- 5) Where a load-bearing wall is perpendicular to the line of joists, the centre of the wall must be no more than 200 mm from the centre of the bearer supporting the joists.
- 6) Cantilevered joists must be specifically designed.
- 7) These tables allow for a ceiling dead load of 260n/m² (12 mm plasterboard on battens).

Steel Joists Profiles for Supercrete™ Soundfloor

Table 5



HST STEEL JOIST DIMENSIONS (mm)										
Section	A	B	C	D	E	F	G	H	J	
Tophat	60 x .95	32	65	108						
	100 x .75	43	91	163	100	45	3	2	10	5
	100 x .95	43	91	163	100	45	3	2	10	5
	120 x .95	43	98	170	120	65	3	2	10	5
	150 x .95	43	110	183	150	100	3	2	10	5
	150 x 1.15	43	110	183	150	100	3	2	10	5
Channel	150/12	65	152	24	8	7	59	10		
	150/15	65	152	24	8	7	59	10		
	150/18	65	152	24	8	7	59	10		
	200/12	75	203	25	8	10	59	12	10	
	200/15	75	203	25	8	10	59	12	10	
	200/18	75	203	25	8	10	59	12	10	
	250/15	85	250	33	10	14	59	12	25	
	250/18	85	250	33	10	14	59	12	25	
	300/15	100	300	38	10	64	59	12	25	
	300/18	100	300	38	10	64	59	12	25	
	350/18	100	350	43	10	92	70	12	25	
	400/20	100	400	48	10	132	75	12	25	

Technical Support

Superbuild International Ltd and its network of Distributors offers technical assistance across New Zealand. Visit www.superbuild.co.nz for your local Distributor who will offer free estimating services; technical support to project architects, engineers, builders and owners.

Health & Safety

Information on any known health risks of our products and how to handle them safely is shown on their package and/or the documentation accompanying them.

Additional information is listed in the Material Safety Data sheet. To obtain a copy, telephone 0800 443 235 or visit www.superbuild.co.nz

Guarantee

Supercrete™ Autoclaved Aerated Concrete products and Supercoat™ Coating System products are guaranteed to be free of defect in material and manufacture.


Installation workmanship and coating application work is guaranteed by the personnel who perform this work.

Substitution of this claddings' listed components is not permissible and if alternative brands, materials or elements are used, this will void all guarantees.

This guarantee excludes all other guarantees and liability for consequential damage or losses in connection with defective cladding, other than those imposed by legislation.

***For further information
on products and
our New Zealand wide
Distributor Network
Phone 0800 443 235 or
visit www.superbuild.co.nz***

Authorised Distributor



Supercrete™

Superbuild International Limited
67 Reid Rd, P.O. Box 2398
Dunedin, New Zealand.
Phone: +64 3 455 1502
Fax: +64 3 456 3587
0800 443 235
www.superbuild.co.nz

**For your nearest distributor of Supercrete™ Products
visit our website www.superbuild.co.nz**

The information presented herein is supplied in good faith and to the best of our knowledge was accurate at the time of preparation. No responsibility can be accepted by Superbuild International Ltd or its staff for errors or omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination of the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied in conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting, or refraining from action as a result of this information. The systems detailed in this design guide are only to be used with Supercrete™ products distributed by Superbuild International Ltd. This literature is not permitted to be used for other types of AAC.

Copyright © Supercrete Limited 2008

Without limiting the rights of the copyright above, no part of this publication shall be reproduced (whether in the same or a different dimension), stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording or otherwise), without the prior permission of the copyright owner.